

MC event generation tutorial

Andy Buckley
University of Glasgow

RAL Advanced Graduate Lectures
15 June 2021





University
of Glasgow



THE ROYAL
SOCIETY

MC generation

- ❖ **MC generation: where theory meets experiment**
 - The fundamental pp collision, *in vacuo*
- ❖ **Components of a fully exclusive SHG chain**
 - QFT matrix element sampling at fixed order in QCD etc.
 - *Dressed* with approximate collinear splitting functions, iterated in factorised Markov-chain “parton showers”
 - FS parton evolution terminated at $Q \sim 1$ GeV: phenomenological hadronisation modelling. Mixed with MPI modelling.
 - Finally particle decays, and other niceties
- ❖ **Today**
 - hands-on tutorial with Pythia8 and MadGraph5
 - for background principles see [my lecture slides](#)
 - introduction to running generators and studying their output
 - generation biasing for efficient phase-space population
 - ME/PS merged generation with extra ME jets
 - BSM model configuration and generation



Generator basics

❖ First, get your Pythia Docker container started

- `$ docker pull hepstore/rivet-pythia`
- `$ docker run -it --rm -v $PWD:/host hepstore/rivet-pythia`



purple = command shell

❖ Pythia8: shower-hadronisation generator (SHG) with many LO processes built-in

- Pythia 8.3 docs: <https://pythia.org/latest-manual/Welcome.html>
- We'll use the "main93" example interface. Open a blank command file: `# nano py8-top.cmnd`
- Add the lines:
 - `Beams:eCM = 13000`
 - `Top:all = on`
 - `Main:writeHepMC = on`
- And run: `# pythia8-main93 -c py8-top.cmnd -o TOP -n 1000`



blue = generator configs

❖ Examine the output

- `less TOP.hepmc`
- Run a basic physics analysis on it: `# rivet -a EXAMPLE TOP.hepmc -H TOP.yoda`
- View the histogram data: `$ less TOP.yoda; # yodals -v TOP.yoda`
- `# rivet-mkhtml TOP.yoda -o /host/rivet-plots-top`
- And point your Web browser at it, e.g. `$ firefox rivet-plots-top/index.html`

More statistics = no more event files

❖ The HepMC ASCII files are very large!

- They waste space, and CPU due to the writing/re-reading time
- Useful for debugging, though

❖ Better that we pass the events to Rivet in memory instead

- `# nano py8-top.cmnd`
- And change to:
 - `Beams:eCM = 13000`
 - `Top:all = on`
 - `Main:runRivet = on`
 - `Main:analyses = MC_TTBAR,MC_JETS,MC_FSPARTICLES,MC_ELECTRONS,MC_MUONS`
- `# pythia8-main93 -c py8-top.cmnd -o TOP -n 5000`
- `# rivet-mkhtml TOP.yoda -o /host/rivet-plots-top`

❖ Inspect the output

- Do the lepton distributions make sense?
- The jets?
- What happens to the statistics at high p_T ?

Jet-event generation

❖ Let's make some inclusive-jet events

- In Pythia, this just means a pp → jj ME. Everything else comes from the PS, especially ISR
- It does remarkably well for that (thanks to a few tricks)
- But mostly we use higher-order generators for the ME nowadays. Py8 is quick, though!

❖ We start with the obvious configuration

- `# nano py8-jets.cmnd`
 - `Beams:eCM = 13000`
 - `HardQCD:all = on`
 - `PhaseSpace:pThatMin = 10`
 - `Main:runRivet = on`
 - `Main:analyses = MC_JETS`
- `# pythia8-main93 -c py8-jets.cmnd -o JETS -n 2000`

❖ View the output

- `# rivet-mkhtml JETS.yoda -o /host/rivet-plots-jets`
- And view: what's happened to the p_T tails and 3rd, 4th jet distributions?
- We can improve this with ME phase-space slicing and/or enhancement


Jet-event slicing

❖ The statistics died off at high p_T

- The unweighted events are asymptotically distributed like the physical $d\sigma/dp_T$
- \Rightarrow far too many low- p_T events for our needs! Rapidly drop below systematics threshold
- Simple solution: stick together several runs in orthogonal *slices* of ME phase-space

❖ Three slices, the top-one open-ended

- Add a max p_T^{hat} to py8-jets.cmnd:
PhaseSpace:pThatMin = 10
PhaseSpace:pThatMax = 50
pythia8-main93 -c py8-jets.cmnd -o JETS0 -n 2000
- Then a min/max pair above that:
PhaseSpace:pThatMin = 50
PhaseSpace:pThatMax = 100
pythia8-main93 -c py8-jets.cmnd -o JETS1 -n 2000
- And a final min-only:
PhaseSpace:pThatMin = 100
pythia8-main93 -c py8-jets.cmnd -o JETS2 -n 1000
- Plot and study: # rivet-mkhtml JETS*.yoda -o /host/rivet-plots-jets




Jet-event enhancement

❖ The statistics work better now, and the correctly xs-normalised sum is smooth

- We still have falling stats in each slice, though: “sawtooth” statistical error
- Can we “continuously slice”? Yes! Sample from $p_{T}^{\text{hat}} \frac{d\sigma}{dp_{T}^{\text{hat}}}$, with weights $1/p_{T}^{\text{hat}}$
- Since LO $2 \rightarrow 2$ process, p_{T}^{hat} is unambiguous

❖ Enhanced dijet generation

- Enable biasing in py8-jets.cmd:
`PhaseSpace:pThatMin = 10`
`PhaseSpace:bias2Selection = on`
`# pythia8-main93 -c py8-jets.cmd -o JETSW -n 2000`
- Pretty-printing of all methods:
`# rivet-mkhtml JETS.yoda:Raw:LineColor=red \
JETS0.yoda:Slice0:LineColor=purple:LineStyle=dashed \
JETS1.yoda:Slice1:LineColor=purple:LineStyle=dashdotted \
JETS2.yoda:Slice2:LineColor=purple:LineStyle=dotted \
JETSW.yoda:Enh:LineColor=orange -o /host/rivet-plots-jets`
- Study the output. Which is better at phase-space coverage?
Compare the numbers of events generated



V+jets production

❖ W/Z+jets are the biggest and most CPU-consuming MC samples at the LHC

- Followed by ttbar, single-top, diboson, ...
- The “classic” development lab for beyond-LO methods, because
 - Born process at 2→1 tree level
 - colour-singlet boson is unproblematic for QCD
 - vector boson: symmetry protection ⇒ small NLO corrections wrt Higgs
 - massive boson = naturally “anchored” scale choices: more stable than massless jets or photons

❖ First, let’s make a Pythia8 version, then go to MG5

- `# nano py8-zmm.cmnd`
 - `Beams:eCM = 13000`
 - `WeakSingleBoson::ffbar2gmZ = on`
 - `23:onMode = off`
 - `23:onIfAny = 13`
 - `Main:runRivet = on`
 - `Main:analyses = MC_JETS`
- `# pythia8-main93 -c py8-zmm.cmnd -o ZMM -n 5000`
- `# mv ZMM.yoda /host/Py-Z.yoda`

V+jets production: MG5

❖ Get the MG5 image and open it in a separate terminal

- `$ docker pull hepstore/rivet-mg5amcnlo`
- `$ docker run -it --rm -v $PWD:/host hepstore/rivet-mg5amcnlo`
`# cd MG5_aMC_v3_1_0/`
`# bin/mg5_aMC`
- MG5 is a fixed-order ME generator that interfaces with Pythia's PS etc.

❖ Generate the lowest-order jet-multiplicity sample

- `> generate p p > mu+ mu-`
`> output PROC-Z`
`> launch`
`> ... (enable Pythia)`
`> quit`
- `# cp -r PROC-Z /host/`
⇒ look at diagrams in the host file browser, xsec in web browser
- `# cd PROC-Z/Events/run_01/`
⇒ look at the LHE (and HepMC) event files:
`# zless unweighted_events.lhe.gz`

V+jets production: MG5 jet-merging

❖ We can also make higher-order MEs (here just tree-level)

- `# bin/mg5_aMC`
 - > `generate p p > mu+ mu-`
 - > `add process p p > mu+ mu- j`
 - > `add process p p > mu+ mu- j j`
 - > `output PROC-ZJJMERGED`
 - > `quit`
- `# cp -r PROC-ZJJMERGED PROC-ZJJ`
 - `# cd PROC-ZJJ`
 - `# nano Cards/proc_card_mg5.dat`
 - `# nano Cards/run_card.dat` ⇒ `set ickkw=0`
 - `# bin/generate_events`
- `# cd ../PROC-ZJJMERGED`
 - `# bin/generate_events`

Add a [QCD] suffix to generate a process at QCD NLO. Slow!!

One-loop matching with MC@NLO; loop and legs merging/matching with FxFx

❖ What's going on???

- The PS makes the different multiplicities overlap in phase-space: have to avoid double-counting
- CKKW(L) and MLM procedures do this by phase-space weights or cuts: we're trying MLM on/off

V+jets production: analysis and comparison

❖ Run Rivet on the (zipped) MG5 HepMC events

- MG5 events have lots of weights, cf. the LHE file. Incorporating scale and PDF variations
- But MG5 doesn't specify a default weight, so we need to identify that by hand:
- ```
rivet -a MC_JETS --nominal-weight='MUF=1.0_MUR=1.0_PDF=247000_MERGING=0.000' \
PROC-Z/Events/run_01/tag_1_pythia8_events.hepmc.gz -H MG-Z.yoda
```
- ```
# rivet -a MC_JETS --nominal-weight='MUF=1.0_MUR=1.0_PDF=247000_MERGING=0.000' \  
PROC-ZJJ/Events/run_01/tag_1_pythia8_events.hepmc.gz -H MG-Zjj-sum.yoda
```
- ```
rivet -a MC_JETS --nominal-weight='MUF=1.0_MUR=1.0_PDF=247000_MERGING=45.000' \
PROC-ZJJMERGED/Events/run_01/tag_1_pythia8_events.hepmc.gz -H MG-Zjj-x.yoda
```
- And plot:  

```
cp /host/Py-Z.yoda .
rivet-mkhtml Py-Z.yoda MG-Z.yoda MG-Zjj-*.yoda -o /host/rivet-plots-z
```

## ❖ Inspect the output

- See how the samples have different kinematics? And the MG5 systematic uncertainty bands?

# BSM physics generation


## ❖ Pythia8 has several built-in models, e.g. Z', SUSY, XD resonances...

- Many are steered just via Py8 parameters — see the manual
- SUSY in particular requires an SLHA file: use `hepstore/rivet-tutorial`
- Set up a command file with
  - `SUSY:all = on`
  - `SLHA:file = gg_g1500_chi100_g-ttchi.slha`
- Run and analyse

## ❖ MG5 is really a generator generator: more flexible

- ⇒ can build new MEs for ~any UFO physics model (as can Sherpa, Herwig)
- E.g. a dark matter model:
  - `> import model DMsimp_s_spin1 --modelname`
  - `> generate p p > xd xd~ j`
- etc. DM mass, coupling can be set in the “param card” = SLHA
- Generate and analyse
- More control can be imposed by fixing new physics couplings at amplitude level e.g. `NP==1` or ME-squared level e.g. `NP^2==1`

`hepstore/rivet-tutorial` is just the `rivet-pythia` Docker image with a few extra tutorial files in the work dir



Since the MG5 conversion to use Python3, you may need to run a ‘convert’ command on your UFO, and re-import. The command-line will advise you if this is the case

# That's it!

- ❖ **Thanks for your time!**
- ❖ You now know how to run two of the most popular LHC event generators at Born and merged/matched levels
- ❖ And how to set up and run any UFO new-physics model
- ❖ This is basically a superpower — use it wisely!
- ❖ And the devil is in the details: black-box mode will only get you so far
- ❖ Sometimes it goes wrong, sometimes... it's complicated
- ❖ **Good luck!**

